


# SERIES 402 STOREFRONT FRAMING



## Shear Block • Screw Spline • Can Receptor

This economical 2" X 4-1/2" flush glaze system is available in both shear block and screw spline fabrication methods. Series 402 Storefront can accommodate all standard 1 3/4" entrances as well as WV410 vents. Vertical mullions will accept steel reinforcement to enhance structural performance.



<p><b>STRUCTURAL LOAD</b> (ASTM E330)</p> <p>→ VISIT <a href="http://EFCOCORP.COM">EFCOCORP.COM</a></p>	<p><b>WATER RESISTANCE</b> (ASTM E547 &amp; E331)</p> <p>12 PSF</p>
<p><b>AIR INFILTRATION</b> (ASTM E283)</p> <p>&lt;0.06 CFM/FT<sup>2</sup></p>	<p><b>CRF</b> (AAMA 1503)</p> <p>N/A</p>
<p><b>U-FACTOR*</b> (ANSI/NFRC 100/200)</p> <p>N/A</p>	<p><b>OITC*</b> (ASTM E90 &amp; E413)</p> <p>SCREW SPLINE: 26 - 29</p>
<p><b>STC*</b> (ASTM E90 &amp; E413)</p> <p>SCREW SPLINE: 30-34</p>	

## STANDARD FEATURES

- Open back and shear block door frames with transom bars and bulb type weather stripping
- Accommodates up to 1-1/8" glazing
- Uniform glazing gasket is used for exterior and interior
- 2-way corner mullions (90° and 135°)
- 3-way corner mullions (T-mullions)
- 0° - 15° and 15° - 30° variable mullions
- Various height intermediate horizontals and sills
- Accessory line of perimeter anchors, pocket fillers, door adaptors, etc.
- Anodized or painted finished available

\* Performance dependent on glass selection. Please contact your EFCO sales rep for project specific performance.